



TECHNICAL CHARACTERISTICS

DESCRIPTION				
Total thickness	EN ISO 24346 (EN 428)	mm	1.50	1.30
Thickness of wearlayer	EN ISO 24340 (EN 429)	mm	0.08	0.08
Weight: Mass per unit area	EN ISO 23997 (EN 430)	g/sqm	2550	2190
Size	EN ISO 24342 (EN 427)	cm	tiles: 30.5 x 30.5	tiles: 30.5 x 30.5
Number of planks / tiles and sqm per box	-	tiles	11 tiles / 1 sqm	11 tiles / 1 sqm
CLASSIFICATION				
Norm / Product specification	-	ISO 10582	ISO 10582	ISO 10582
European classification	EN ISO 10874 (EN 685)	class	22	22
Fire rating - Classification	EN 13501-1	class	Bfl S1	Bfl S1
Static electrical prospersity	EN 1815	-	< 2 kV	< 2 kV
Slip resistance wet: ramp test with oil	DIN 51130	class	R9 / R10	R9 / R10
PERFORMANCE				
Wear Group	EN 649	group	T	T
Dimensional stability after exposure to heat	EN ISO 23999 (EN 434)	%	< 0.40	< 0.40
Residual Indentation	EN ISO 24343-1 (EN 433)	mm	0.04	0.04
Impact sound insulation	EN ISO 717-2	dB	3	3
Room impact noise	NF S 31074	class	C	C
Thermal conductivity	EN ISO 10456 (EN 12524)	W(m.k)	0.25	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6	≥ 6
Garantee for residential use	-	year	7	3
ENVIRONMENT / INDOOR AIR QUALITY				
TVOC after 28 days	ISO 16000-6	µg/m ³	< 100	< 100
VOC rating (French norm)	-	-	A+	A+
CE MARKING				
	EN 14041			

Areas of use: domestic use



DULCE HOGAR